

Watt Industries UK Ltd

**BRONZE GATE VALVES
MOV250 PN20**

Bronze Gate valves PN20 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Ends Screwed Female BSP Taper, Handwheel operated.

Manufactured in accordance with BS5154 Series B 20 bar.

Temperature range -10°C to +100°C rated to 9 bar @ 180°C.

Test Pressure (hydraulic) Shell: 30 bar

Test Pressure (hydraulic) Seat: 22 bar

Part number	End Connection	Box Qty
M12299	3/8"	
M12300	1/2"	
M12301	3/4"	
M12302	1"	
M12303	1-1/4"	
M12304	1-1/2"	
M12305	2"	
M12306	2-1/2"	
M12307	3"	



**BRONZE GATE VALVES
MOV250 PN20**

Bronze Gate valves PN20 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Ends Screwed Female BSP Taper, Lockshield operation.

Manufactured in accordance with BS5154 PN20 Series B.

20 bar from -10°C to +100°C, rated to 9 bar @ 180°C.

Test Pressure (hydraulic) Shell: 30 bar

Test Pressure (hydraulic) Seat: 22 bar

Part number	End Connection	Box Qty
M12400	1/2"	
M12401	3/4"	
M12402	1"	
M12403	1-1/4"	
M12404	1-1/2"	
M12405	2"	
M12406	2-1/2"	
M12407	3"	



**BRONZE GATE VALVES
MOV100 PN20**

Bronze Gate valves PN20 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Compression Ends, Handwheel operated.

Manufactured in accordance with BS5154 PN20 Series B.

20 bar from -10°C to +100°C, rated to 9 bar @ 180°C.

Test Pressure (hydraulic) Shell: 30 bar

Test Pressure (hydraulic) Seat: 22 bar

Part number	End Connection	Box Qty
M12500	15mm	
M12501	22mm	
M12502	28mm	
M12503	35mm	
M12504	42mm	
M12505	54mm	



**BRONZE GATE VALVES
MOV100 PN20**

Bronze Gate valves PN20 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Compression Ends, Lockshield operation.

Manufactured in accordance with BS5154 PN20 Series B.

20 bar from -10°C to +100°C, rated to 9 bar @ 180°C.

Test Pressure (hydraulic) Shell: 30 bar

Test Pressure (hydraulic) Seat: 22 bar

Part number	End Connection	Box Qty
M12600	15mm	
M12601	22mm	
M12602	28mm	
M12603	35mm	
M12604	42mm	
M12605	54mm	



Watt Industries UK Ltd

BRONZE GATE VALVES

MOV288 PN20

Bronze Gate valves PN20 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Solder Ends, Handwheel operated.

Manufactured in accordance with BS5154 PN20 Series B.

20 bar from -10°C to +100°C, rated to 9 bar @ 180°C.

Test Pressure (hydraulic) Shell: 30 bar

Test Pressure (hydraulic) Seat: 22 bar

Part number	End Connection	Box Qty
M12700	15mm	
M12701	22mm	
M12702	28mm	
M12703	35mm	
M12704	42mm	
M12705	54mm	
M12706	67mm	



BRONZE GATE VALVES

MOV288 PN20

Bronze Gate valves PN20 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Solder Ends, Lockshield operation.

Manufactured in accordance with BS5154 PN20 Series B.

20 bar from -10°C to +100°C, rated to 9 bar @ 180°C.

Test Pressure (hydraulic) Shell: 30 bar

Test Pressure (hydraulic) Seat: 22 bar

Part number	End Connection	Box Qty
M12800	15mm	
M12801	22mm	
M12802	28mm	
M12803	35mm	
M12804	42mm	
M12805	54mm	



BRONZE GATE VALVES

MOV110 PN16

Bronze Gate valves PN16 rated, Non-Rising Stem, Screwed Bonnet, Solid Wedge Disk, Ends Flanged & Drilled BS4504 PN16, Handwheel operated.

Manufactured in accordance with BS5154 PN16 Series B.

16 bar from -10°C to +100°C, rated to 7 bar @ 180°C.

Test Pressure (hydraulic) Shell: 24 bar

Test Pressure (hydraulic) Seat: 17.6 bar

Part number	End Connection	Box Qty
M12900	2"	1
M12901	2-1/2"	1
M12902	3"	1
M12903	4"	1

