

## Watts Industries UK Ltd

### CAST IRON GATE VALVES - MOV263 - PN16

Cast Iron Gate valves Non-Rising Stem, Inside Screw, flanged BS4504 PN16, Bronze Trim, Handwheel operated.

Manufactured in accordance with BS5150 PN16.

16 bar from -10°C to +120°C, 12.8 bar at +200°C.

Test Pressure (hydraulic) Shell: 24 bar  
Test Pressure (hydraulic) Seat: 17.6 bar

| Part number | End Connection | Box Qty |
|-------------|----------------|---------|
| M14800      | 2"             | 1       |
| M14801      | 2-1/2"         | 1       |
| M14802      | 3"             | 1       |
| M14803      | 4"             | 1       |
| M14804      | 5"             | 1       |
| M14805      | 6"             | 1       |
| M14806      | 8"             | 1       |
| M14807      | 10"            | 1       |
| M14808      | 12"            | 1       |



### CAST IRON GATE VALVES - MOV263 - PN6

Cast Iron Gate valves Non-Rising Stem, Inside Screw, flanged BS4504 PN6, Bronze Trim, Handwheel operated.

Manufactured in accordance with BS5150 PN6.

16 bar from -10°C to +120°C, 12.8 bar at +200°C.

Test Pressure (hydraulic) Shell: 9 bar  
Test Pressure (hydraulic) Seat: 6.6 bar

| Part number | End Connection | Box Qty |
|-------------|----------------|---------|
| M14820      | 2"             | 1       |
| M14821      | 2-1/2"         | 1       |
| M14822      | 3"             | 1       |
| M14823      | 4"             | 1       |
| M14824      | 5"             | 1       |
| M14825      | 6"             | 1       |



### CAST IRON SWING CHECK VALVES - MOV30 - PN16

pattern, flanged BS4504 PN16, Bronze Trim, bolted cover.

16 bar from -10°C to +120°C.

Test Pressure (hydraulic) Shell: 24 bar  
Test Pressure (hydraulic) Seat: 17.6 bar

| Part number | End Connection | Box Qty |
|-------------|----------------|---------|
| M14900      | 2"             | 1       |
| M14901      | 2-1/2"         | 1       |
| M14902      | 3"             | 1       |
| M14903      | 4"             | 1       |
| M14904      | 5"             | 1       |
| M14905      | 6"             | 1       |
| M14906      | 8"             | 1       |
| M14907      | 10"            | 1       |
| M14908      | 12"            | 1       |



### CAST IRON Y TYPE STRAINER - MOV821 - PN16

Cast Iron Y Type Strainer, flanged BS4504 PN16, stainless steel mesh 1.6mm diameter. Interim cleaning by 3/4" drain plug. Two gauge ports (gauges supplied at extra cost) Manufactured in accordance with BS5150 PN16.

16 bar from -10°C to +120°C.

Test Pressure (hydraulic) Shell: 24 bar  
Test Pressure (hydraulic) Seat: 17.6 bar

| Part number | End Connection | Box Qty |
|-------------|----------------|---------|
| M15600      | 2"             | 1       |
| M15601      | 2-1/2"         | 1       |
| M15602      | 3"             | 1       |
| M15603      | 4"             | 1       |
| M15604      | 5"             | 1       |
| M15605      | 6"             | 1       |
| M15606      | 8"             | 1       |
| M15607      | 10"            | 1       |
| M15608      | 12"            | 1       |

