

Watts Industries UK Ltd

BRONZE GLOBE VALVES MOV451 PN32

Bronze Globe valves PN32 rated, Rising Stem, Screwed-in Bonnet, Teflon Disk, Ends Screwed Female BSP Parallel, Handwheel operated.

Manufactured in accordance with BS5154 PN32 Series B.

32 bar from -10°C to 100°C, rated to 14 bar @ 198°C.

Test Pressure (hydraulic) Shell: 48 bar

Test Pressure (hydraulic) Seat: 35.2 bar

Part number	End Connection	Box Qty
M13300	1/2"	
M13301	3/4"	
M13302	1"	
M13303	1-1/4"	
M13304	1-1/2"	
M13305	2"	



BRONZE NEEDLE GLOBE VALVES PN32

MOV759

Bronze Needle Globe valves PN32 rated, Rising Stem, Screwed-in Bonnet, Metal to Metal Seat & Needle Disk, Ends Screwed Female BSP Parallel, Handwheel operated.

Manufactured in accordance with BS5154 PN32 Series B.

32 bar from -10°C to 100°C, rated to 14 bar @ 198°C.

Test Pressure (hydraulic) Shell: 48 bar

Test Pressure (hydraulic) Seat: 35.2 bar

Part number	End Connection	Box Qty
M13400	1/4"	
M13401	3/8"	
M13402	1/2"	
M13403	3/4"	
M13404	1"	
M13405	1-1/4"	
M13406	1-1/2"	
M13407	2"	



BRONZE NEEDLE GLOBE VALVES MOV760 PN32

Bronze Needle Globe valves PN32 rated, Rising Stem, Screwed-in Bonnet, Metal to Metal Seat & Needle Disk, Ends Screwed Female BSP Parallel, Lockshield operation.

Manufactured in accordance with BS5154 PN32 Series B.

32 bar from -10°C to 100°C, rated to 14 bar @ 198°C.

Test Pressure (hydraulic) Shell: 48 bar

Test Pressure (hydraulic) Seat: 35.2 bar

Part number	End Connection	Box Qty
M13500	1/4"	
M13501	3/8"	
M13502	1/2"	
M13503	3/4"	
M13504	1"	



BRONZE GLOBE VALVES MOV935 PN40

Bronze Globe valves PN40 rated, Rising Stem, Screwed-in Bonnet, Stainless Steel Seat & Disk, Ends Screwed Female BSP Parallel, Handwheel operated.

Manufactured in accordance with BS5154 PN32 Series B.

40 bar from -10°C to 120°C, rated to 17.5 bar @ 260°C.

Test Pressure (hydraulic) Shell: 60 bar

Test Pressure (hydraulic) Seat: 44 bar

Part number	End Connection	Box Qty
M13600	1/2"	
M13601	3/4"	
M13602	1"	
M13603	1-1/4"	
M13604	1-1/2"	
M13605	2"	




Watts Industries UK Ltd

**BRONZE GLOBE VALVES
MOV400 PN16**

Bronze Globe valves PN16 rated, Rising Stem, Screwed-in Bonnet, Metal to Metal Seat & Disk, Ends Flanged & Drilled BS4504 PN16, Handwheel operated.

Manufactured in accordance with BS5154 PN16 Series B. 16 bar from -10°C to 100°C, rated to 7 bar @ 170°C.
Test Pressure (hydraulic) Shell: 24 bar
Test Pressure (hydraulic) Seat: 17.6 bar

Part number	End Connection	Box Qty
M13700	1/2"	
M13701	3/4"	
M13702	1"	
M13703	1-1/4"	
M13704	1-1/2"	
M13705	2"	
M13706	2-1/2"	
M13707	3"	
M13708	4"	



**BRONZE STOPCOCK VALVES
MOV052 PN20**

Bronze Stopcock BS1400 LG2, Screwed-in Bonnet, NBR Disk Gasket, Compression Ends, Crutch top operation.

Part number	End Connection	Box Qty
M13800	15mm	
M13801	22mm	
M13802	28mm	
M13803	35mm	
M13804	42mm	
M13805	54mm	

