

2kW

inverter portable generator

Specification:

Engine type	Forced air-cooled, four-stroke
Starting system	Recoil starter
Displacement(cm ³)	79
Fuel capacity (L)	5
Continuous running time(h)	6-20
Noise level dB(A)/7m	52-59
Max.output (KVA)	2
Rated AC output (KVA)	1.8
THD	<2.5%
Parallel operation	Optional
N.W.(Kg)	Optional 680pcs/40'HQ 544pcs/40'GP 272pcs/20'GP
Container load	
Certificate	CE,EMC,EPA, CARB



Main features:

- 1) 15% lower fuel consumption than competitors;
- 2) 20% larger fuel tank capacity (5L) than competitors;
- 3) 40% longer continuous running hours than competitors, from 6-20 hrs;
- 4) 52-59dbA/7m noise level only, ultra silent;
- 5) 19.8kgs weight only, portable and lightweight;
- 6) 8 minutes only to access to any part for easy inspection, maintenance or repair;
- 7) 2kw stable and reliable output, without power reduction all the time;
- 8) 50°C high ambient temperature environment workable;
- 9) Direct gravity fuel supply, without fuel pump for better starting;
- 10) Simple operation due to all control units integrated in one-side control panel;
- 11) Patented fully-enclosed outer structure enhances intensity and stops noise leakage;
- 12) Patented inner structure of dual-fan, dual-air channel, dual-muffler, and double-layer acoustic hood ensures better cooling and lower noise.

