

BWT Bewamat B



Reduce



Improve



Protect

Water softener < 3 m³/h

Flow rate: **1.4 to 1.8 m³/h**

Resin volume: **3.2 to 21 L**



BWT Best
Water App



Download on the
App Store

GET IT ON
Google Play



TECHNICAL BENEFITS

- » **Power Failure Protection:** settings saved; auto regeneration after outage. AQA Safe valve function.
- » **Controlled hygiene:** automatic electrolysis self-disinfection; 72-hour anti-stagnation cycle.
- » **Performance and safety:** Efficient water and salt use, volume-controlled backwash, precise brine meter.
- » **Remote monitoring** via Best Water Home App.
- » **Easy to install.**

Operation

The new BWT Bewamat B series is a fully automatic simplex softener line, renowned for its robust performance, reliability and efficient silky-soft Pearlwater production. The Bewamat B series features Bluetooth, WiFi, and IoT integration, allowing easy connection to the BWT Best Water Home App for softener monitoring, AQA alerts, and maintenance notifications.

Applications

Three models available (10B, 25B, and 75B) offering different capacities suitable for households of 1 to 10 people. Designed for both decentralised and centralised (basement) installations. Prevents limescale damage, reduces detergent and shampoo needs, saves money, and supports a greener home.

	BWT BEWAMAT 10 B	BWT BEWAMAT 25 B	BWT BEWAMAT 75 B
Connection width	DN 32	DN 32	DN 32
Flow rate according acc. to EN 14743	1.4 m ³ /h (6.1 gpm)	1.4 m ³ /h (6.1 gpm)	1.8 m ³ /h (7.9 gpm)
Nominal capacity	30 m ³ × °dH (3.6 mol)	25 m ³ × °dH (4.5 mol)	75 m ³ × °dH (13.4 mol)
Operating pressure min./max.	2/8 bar (29/116 psi)	2/8 bar (29/116 psi)	2/8 bar (29/116 psi)
Salt tank	14 kg	15 kg	50 kg
Salt consumption per regeneration	1 kg	1.2 kg	3.5 kg
Dimensions (H × W × D)	530 × 290 × 430 mm	640 × 390 × 560 mm	1090 × 390 × 560 mm
ITEM CODE	125687412	125686906	125686907

The key highlights

- » AQA safe valve prevents water damage caused by flushing water in the event of a power failure.
- » AQA Alert Warning Functions - Real-time app alerts for connected devices.
- » AQA Watch - Detects leaks or faults and notifies users via app.
- » AQA Volume - Warns in app if excessive softened water enters unit.
- » AQA Max Flow - Immediate alert if water inflow exceeds 3,500 l/h.
- » Tested and fully DVGW-compliant.